

ICEFIRE-ET

Enterprise Tablet PC

- 10.4" TFT 350 cd/m² XGA LCD with Multi-resistive touch
- Intel® Atom™ D525 dual core platform
- Powered by Windows® Embedded Standard 7 P
- 3M pixels camera with LED flash
- Bluetooth, Wi-Fi, Ethernet LAN
- Dual hot swappable batteries
- Optional Docking Station / Smart card reader



Application


Enterprise Mobility

Using technology to quickly move products helps save you time, increasing productivity. The right technology enables the flow of information between handheld devices used by your workers and your core business systems. ICEFIRE –ET mobile computing, wireless local area networks (WLANs) and management software to speed the transfer of data and optimize your working mobility in logistic and warehousing environment



Home Automation and Education

Instead of rugged design makes tablet PC heavy and suburb the stylish and ergonomic design makes ICEFIRE-ET perfect for home automation control system and E-education device.



Logistic and Warehouse

Enhancing on-duty people work force and mobility, tablet PC brings you more efficiency than you can imagine. Keep all the data and information in ICEFIRE-ET and transmit via wireless communication can provide your real-time responds without any lost.



Specifications

Model	ICEFIRE-ET	
Display	LCD Size	10.4" TFT LCD
	Brightness (cd/m ²)	350 cd/m ²
	Max Resolution	1024 x 768 pixels XGA
	Viewing Angle	88/88/88/88 Deg.
	Touch Screen	Resistive Support Multi-touch and Gesture
System	CPU	Intel® Atom™ D525 1.8GHz
	Chipset	Intel® ICH8M
	Operation System	Microsoft® Windows® Embedded Standard 7 P
	Memory	2GB DDR3 SDRAM 1333MHz
Communication	Wireless LAN	Wi-Fi® 802.11a/b/g/n
	Bluetooth	Bluetooth® V2.1+ EDR (Class II)
Data Collection	Camera	3M pixel and LED Light
Indicator & Buttons	LED Indicator	Power/ Wifi/Bluetooth/ Battery Status LED
	Keys	5-way Navigation key Camera/Wi-Fi/Bluetooth/SAS/Function Key
I/O Interface	USB	1 x USB 2.0 FULL SPEED
	LAN	1 x 10/100M LAN
	Audio	1 x 2W Speaker 1 x Mic in
Power	Power Adapter	12V@5A@60W
	Docking Power Adapter	19V@4.74A@90W
	Battery	11.1V 1880mAh Li-ion Battery
Environment	Operating Temperature	0°C to +40°C
	Storage Temperature	-10°C to +60°C
	Humidity	5%~95% non-condensing
	Drop Survival	1.0 M
	Environmental Protection	Front Panel IP64 compliant
	Certification	UL/CE/FCC,
Physical Characteristics	Dimensions (LxWxH) (mm)	270 x 265 x 29
	Weight	1,788g

Ordering Information

With SSD&OS

Part No.	Description
ICEFIRE-T10A-ET/2G-32S-R10	10.4" TFT-LCD 350 cd/m ² XGA Industrial Mobile Clinical Assistant with Dual-core Intel® Atom™ D525 1.8GHz CPU Integrate Resistive Touch, 2GB DDR3 RAM, 802.11 a/b/g/n Wireless, Bluetooth, 3M Pixels Camera, 32G SSD, WS7P RoHS

Packing List

Item	Part No.
Stylus	XTR104-0002-RS
Battery Pack-B	31603-000020-RS
Non-Medical-grade Power Adapter (12V/60W)	63000-FSP060DBAB1553-RS
User's Manual CD ROM	7B000-000552-RS

Dimensions (Unit: mm)

