


Europac Pro Subracks




Kit, "heavy", shielded, for backplane mounting



Without front handle 06102008 With front handle 0611001



6 U



D = overall depth, D1 = insertion depth, D2 = board depth = D1 - 15 mm



Rear horizontal rail for backplane mounting with insulation strip



ServicePLUS see page 6.16

- Subrack with side panel type H ("heavy"), 19" bracket is firmly fixed to side panel (tox-cold welded)
- Rear horizontal rail for backplane mounting with insulation strip
- Shielding typically 40 dB at 1 GHz, 30 dB at 2 GHz, assuming that the front is closed with sealed front panels
- Shock and vibration resistance up to 5 g
- Installed load up to 15 kg
- Versions with/without front handles

NEW

Delivery comprises (Kit)

| Item | Qty | | Description |
|------|-----|-----|---|
| | 3 U | 6 U | |
| 1 | 2 | 2 | Side panel type H, Al, 2 mm, passivated, with 19" support bracket (tox-cold welded); for textile EMC gasket |
| 2 | 2 | 2 | Rear corner profile for textile EMC gasket |
| 3 | 2 | 2 | Front horizontal rail (H-KD) |
| 3 a | 2 | 2 | Rear horizontal rail (H-KD) |
| 3 b | 2 | 2 | Rear horizontal rail (H-ST) |
| 3 c | - | 1 | Rear horizontal rail centre (ST) |
| 4 | 6 | 8 | Threaded insert (pre-fitted) |
| 5 | 2 | 2 | Perforated strip (pre-fitted) |
| 6 | 2 | 4 | Insulation strip (pre-fitted) |
| 7 | 2 | 2 | EMC cover plate |
| 8 | 1 | 1 | EMC gasketing material (pre-fitted) |
| 9 | 1 | 1 | EMC rear panel |
| 10 | 1 | 1 | Fixing material kit, user manual |
| 11 | 2 | 2 | Front handle (on version with front handle only) |

Order Information

| Height U | Width HP | Depth D mm | Depth D1 mm | Part no. with front handle | Part no. without front handle |
|----------|----------|------------|-------------|----------------------------|-------------------------------|
| 3 | 84 | 235 | 175/235 | 24567-172 | 24563-172 |
| 3 | 84 | 295 | 175/235/295 | 24567-173 | 24563-173 |
| 3 | 84 | 355 | 175/235/295 | 24567-174 | 24563-174 |
| 6 | 84 | 235 | 175/235 | 24567-472 | 24563-472 |
| 6 | 84 | 295 | 175/235/295 | 24567-473 | 24563-473 |
| 6 | 84 | 355 | 175/235/295 | 24567-474 | 24563-474 |

Accessories

19" assembly kit (screw, washer, nut) (8 x screws, 8 x plastic washers, 8 x cage nuts) **21100-435**

Guide rails (standard), ESD clips

| Depth D2 mm | Qty/PU piece | Part no. |
|-------------|--------------|------------------|
| 160 | 10 | 24560-351 |
| 220 | 10 | 24560-353 |
| 280 | 10 | 24560-379 |

ESD clip for guide rails PU 50 pieces

ESD clip for guide rails PU 50 pieces **24560-255**

Torx panhead screw, for extra bolting of the guide rails, 2.5 x 9.3, zinc-plated, PU 100 pieces; torque max. 0.2 Nm **24560-141**

Note

- ServicePLUS configuration from page 6.16

Koning & Hartman B.V.

Energieweg 1
2627 AP Delft
P.o. box 5080
2600 GB Delft
The Netherlands

T +31 (0)15 260 99 06
F +31 (0)15 261 91 94
E info@koninghartman.com
I koninghartman.com

CoC 34.222.312
VAT NL.8141.69.144.B.01

F. van Lanschot Bankiers
69.94.03.383

Heeft u vragen over dit product, of zoekt u een subrack in andere afmetingen of uitvoering, neem dan contact op met onze specialisten op tel 015-260 9803 of email naar sales.delft@koninghartman.com