

# VTC Series Accessories

## VTK 61B



### Main Features

- ♦ Back up smart battery + charger
- ♦ Thermal control
- ♦ SMBus interface
- ♦ For VTC series

### Specifications

#### Back up smart battery + Charger

- ♦ Battery back-up for 4 hours in system full loading (1.4A/ 12V)
- ♦ Battery status is detectable by S/ W
- ♦ 2 x LED indicators for the battery status
- ♦ Input voltage: 6-36V with ignition control
- ♦ Output voltage: 12V with ignition for VTC Series System.

#### Operation Temperature

- ♦ 0°C to +55°C

#### Certification

- ♦ CE approval
- ♦ FCC

#### Dimensions

- ♦ 238mm (W) x 150mm (L) x 25mm (H)
- ♦ 1.75 Kg (3.86 Lb)

### Ordering Information

- ♦ VTK61B (P/N: 10VK0061B00X0)

## VTK 33V



### Main Features

- ♦ Unique 3D X-Y-Z axis anti-vibration design
- ♦ Integrated fan x 2
- ♦ For VTC 3300E, VTC 6000, VTC 6100, VTC 6110

### Specifications

#### Vibration

- ♦ VTC 3300E, VTC 6000, VTC 6100, VTC 6110 (operating)  
2G@10~500 Hz with Automotive HDD  
3G@5~500 Hz random with CF

#### Thermal

- ♦ 2 x fan (60 x 60mm, 12V) for lowering surface temperature of VTC series

#### Dimensions

- ♦ 320mm (W) x 180mm (L) x 86.5mm (H)
- ♦ 1.48 Kg (3.3 Lb)

### Ordering Information

- ♦ VTK 33V (P/N: 10VK0033V00X0)

# VTK 61P



## Main Features

- IP65 compliant, anti-dust & anti-water protection kit
- Cables and antennas can be connected on VTC 6000 with external peripheral devices
- LED status is readable through window
- VTK 61P Designed for VTC 6100/ VTC 6110/ VTC 6120/ VTC 6200-NI

## Specifications

### Dimensions

- 320mm (L) x 176mm (W) x 50mm (H)
- 2.8 Kg (6.18 Lb)

## Ordering Information

- VTK 61P (P/N: 10VK0061P00X0)