

# WADE-8075/76

Leading Intel® Atom™ D525 1.8GHz / N455 1.67GHz Processor based Mini-ITX with DC12V input, DDR3 SDRAM, Dual display, Dual Gigabit Ethernet, Three SATA, Four COM and Six USB ports



## FEATURES

- Intel® Atom™ D525 1.8GHz / N455 1.67GHz Processor
- Intel® ICH8M Chipset
- Two 204-Pin SO-DIMMs support single channel DDR3 SDRAM up to 4GB
- Dual Display by VGA / LVDS(24bits or 18bits)
- One PCI-Express x 1, one PCI expansion slot and one Mini-PCIe socket (with USB + PCIe1 signal)
- Three RS-232 ports and one RS232/422/485 port

The WADE-8075/WADE-8076 built with Intel® ICH8M chipset and takes advantage of Intel® ATOM™ D525/N455 processor technologies that can support DDR3 memory, Dual Gigabit Ethernet ports, one expansion PCI-Express x1 slot, one PCI

slot and one Mini PCI socket. WADE-8075/WADE-8076 is the ideal platform for POS, Lottery, Medical, Gaming, high resolution digital signage, surveillance security monitoring, and Kiosk applications.


SYSTEM	
CPU	Intel® Atom™ D525/N455 processor
DMI	4.8 GT/s-6.4 GT/s (Full-Duplex)
BIOS	AMI uEFI BIOS (SPI ROM)
System Chipset	Intel® ICH8M
System Memory	Two 204-Pin SO-DIMM support single channel DDR3 SDRAM up to 4GB
Storage	3 x Serial ATA connector high-speed data transfers at up to 3Gb/s
SSD	One compact flash
Watchdog Timer	Programmable via S/W from 1sec. ~ 255min.
H/W Monitor	Monitoring Temperature, Voltage, and cooling fan status Auto throttling control when CPU overheats
GPIO	Onboard programmable 16-bit Digital I/Os(8x In/Out)
Expansion	- One PCI slot and One PCI-Ex1 slot - One Mini-PCIe slot

MECHANICAL & ENVIRONMENTAL	
Power Requirement	TBD
Operation Temperature	0-60°C
Operating Humidity	5-95% non-condensing
Size (L x W)	6.69" x 6.69" (170mm x 170mm)
Weight	0.95lbs (0.43 Kg)


I/O	
MIO	- 2 x RS232 5V/12V selectable - 1 x RS232 5V/12V selectable, with header - 1 x RS232/422/485 5V/12V selectable - 1x KB/MS with header
IrDA	N/A
USB	4 x USB 2.0 ports and 2 x USB 2.0 with header
Audio Interface	Mic-in, Line-in/out, Line out with header
Ethernet Interface	Dual Gigabit Ethernet(RTL8111D*2)

DISPLAY	
Chipset	Intel® ICH8M
Display Memory	Intel® DVMT
Resolution	- Analog Display: Up to 2048 x 1536 - Digital LVDS: Up to 1280*1024 (WADE-8075) Up to 1366*768 (WADE-8076)
LVDS	- Dual Channel 24-bit (WADE-8075) - Single Channel 18-bit(WADE-8076)

## REAR I/O



## SOLDER SIDE



## ORDERING GUIDE

### ■ WADE-8075

Intel® Atom™ D525 1.8GHz Processor based Mini-ITX with DC12V input, DDR3 SDRAM, VGA and 24bits LVDS, Dual Gigabit Ethernet, Three SATA, Four COM and Six USB ports

### ■ WADE-8076

Intel® Atom™ N455 1.67GHz Processor based Mini-ITX with DC12V input, DDR3 SDRAM, VGA and 18bits LVDS, Dual Gigabit Ethernet, Three SATA, Four COM and Six USB ports



### Portwell, Inc. (Headquarters)

No. 242, Bo-Ai St., Shu-Lin City,  
Taipei County 238, Taiwan  
Tel: +886-2-77318888  
Fax: +886-2-77319888  
E-mail: info@portwell.com.tw  
http://www.portwell.com.tw

### American Portwell

Fremont CA Tel: +1-510-403-3399  
Woodstock GA Tel: +1-770-926-9920  
E-mail: info@portwell.com  
http://www.portwell.com

### Portwell Japan, Inc.

Tokyo Tel: +81-3-5298-8071  
Osaka Tel: +81-6-4807-7721  
E-mail: info@portwell.co.jp  
http://www.portwell.co.jp

### Beijing Portwell

Beijing Tel: +86-10-82701616  
Shanghai Tel: +86-21-3222-0505  
Shenzhen Tel: +86-755-8621-7695  
E-mail: info@portwell.com.cn  
http://www.portwell.com.cn

### Portwell-Laxsons India

Tel: +91-22-2685-9911  
E-mail: info@portwellaxsons.com  
http://www.portwellaxsons.com

### European Portwell

Tel: +31-252-620790  
E-mail: info@portwell.nl  
http://www.portwell.nl

### Portwell (UK) Ltd.

Tel: +44(0)1235-750760  
E-mail: info@portwell.co.uk  
http://www.portwell.co.uk